

US010722089B2

# (12) United States Patent

# Conrad

#### (54) SURFACE CLEANING APPARATUS

- (71) Applicant: Omachron Intellectual Property Inc., Hampton (CA)
- (72) Inventor: Wayne Ernest Conrad, Hampton (CA)
- (73) Assignee: **Omachron Intellectual Property Inc.**, Hampton, Ontario (CA)
- (\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 248 days.
- (21) Appl. No.: 15/937,333
- (22) Filed: Mar. 27, 2018

#### (65) **Prior Publication Data**

US 2019/0298133 A1 Oct. 3, 2019

(51) Int. Cl.

(2006.01)
(2006.01)
(2006.01)

- (58) Field of Classification Search
  - CPC ......... A47L 9/2836; A47L 5/24; A47L 9/2805; A47L 9/10; A47L 9/2884; H01M 2/1055; H01M 10/613; H01M 10/6235; H01M 10/6563; H01M 10/63; H01M 10/643; H01M 10/6556; H01M 10/6566; H01M 2220/30

See application file for complete search history.

# (10) Patent No.: US 10,722,089 B2 (45) Date of Patent: Jul. 28, 2020

## (56) **References Cited**

# U.S. PATENT DOCUMENTS

1,871,624 A	A 8/1932	Loewinsohn				
6,457,205 B	31 * 10/2002	Conrad A47L 5/225				
		15/319				
7,120,965 B	32 10/2006	Hisano et al.				
7,353,565 B	32 * 4/2008	Hisano A47L 9/00				
		15/413				
8,475,507 B	32 7/2013	Dewey et al.				
8,776,310 B	32 7/2014	Genn et al.				
(Continued)						

#### FOREIGN PATENT DOCUMENTS

CN	205671987 U	11/2016
CN	106343919 A	1/2017
	(Cont	inued)

#### OTHER PUBLICATIONS

TotalPatent: English machine translation of DE102014200663, published on Jul. 31, 2014.

#### (Continued)

Primary Examiner - David Redding

(74) Attorney, Agent, or Firm — Philip C. Mendes da Costa; Bereskin & Parr LLP

# (57) **ABSTRACT**

A surface cleaning apparatus has a first air flow path extending from a dirty air inlet to a clean air outlet with a suction motor and an air treatment member positioned in the first air flow path. A second air flow path extends from an ambient air inlet to a secondary air outlet. An energy storage chamber having at least one energy storage member is positioned in the second air flow path. Ambient air can be drawn through the second air flow path to promote cooling of the energy storage members. A fan unit and or a venture can be used to draw ambient air into the second airflow path.

#### 19 Claims, 17 Drawing Sheets



# (56) **References Cited**

# U.S. PATENT DOCUMENTS

8,994,339	B1 *	3/2015	Kam H02J 7/0029
			320/150
9,370,285	B2	6/2016	Visel et al.
2004/0216266	A1 $*$	11/2004	Conrad A47L 5/28
			15/412
2005/0017681	A1*	1/2005	Ogishima A47L 9/2805
			320/112
2005/0202310	A1*	9/2005	Yahnker B25F 5/008
			429/62
2007/0163073	A1	7/2007	Sepke et al.
2012/0159736	A1*	6/2012	Huber A47L 9/00
			15/339
2014/0208538	A1	7/2014	Visel et al.
2017/0035261	A1*	2/2017	Lauer A47L 5/24
2017/0280950	A1	10/2017	Nam et al.
2017/0280951	A1	10/2017	Nam et al.
2017/0280952	A1	10/2017	Nam et al.
2017/0280959	A1	10/2017	Nam et al.
2017/0296007	A1	10/2017	Warren et al.
2017/0296958	A1	10/2017	Nam et al.
2017/0303754	A1*	10/2017	Conrad A47L 9/1683
2017/0332860	A1	11/2017	Nam et al.
2019/0020202	A1*	1/2019	Wan H01M 10/446

# FOREIGN PATENT DOCUMENTS

CN	106618374 A	5/2017
CN	106618375 A	5/2017
DE	102014200663 A1	7/2014
JP	2002065535 A	3/2002
WO	2014195711 A1	12/2014
WO	2017013391 A1	1/2017
WO	2017013392 A2	1/2017
WO	2017181041 A2	10/2017

# OTHER PUBLICATIONS

TotalPatent: English machine translation of JP2002065535, published on Mar. 5, 2002.

TotalPatent: English machine translation of CN205671987, published on Nov. 9, 2016.

TotalPatent: English machine translation of CN106618375, published on May 10, 2017.

TotalPatent: English machine translation of CN106618374, published on May 10, 2017.

TotalPatent: English machine translation of CN106343919, published on Jan. 25, 2017.

\* cited by examiner































FIG. 13D







# SURFACE CLEANING APPARATUS

# FIELD

This disclosure relates generally to surface cleaning apparatus such as hand vacuum cleaners, upright vacuum cleanesers, stick vacuum cleaners or canister vacuum cleaners, and in particular portable surface cleaning apparatus, such as hand vacuum cleaners, with onboard energy sources that are air cooled.

# INTRODUCTION

The following is not an admission that anything discussed below is part of the prior art or part of the common general <sup>15</sup> knowledge of a person skilled in the art.

Various types of surface cleaning apparatus are known, including upright surface cleaning apparatus, canister surface cleaning apparatus, stick surface cleaning apparatus, central vacuum systems, and hand carriable surface cleaning <sup>20</sup> apparatus such as hand vacuums. Further, various designs for cyclonic surface cleaning apparatus, including battery operated cyclonic hand vacuum cleaners are known in the art.

#### SUMMARY

The following introduction is provided to introduce the reader to the more detailed discussion to follow. The introduction is not intended to limit or define any claimed or as 30 yet unclaimed invention. One or more inventions may reside in any combination or sub-combination of the elements or process steps disclosed in any part of this document including its claims and figures.

In accordance with one aspect of this disclosure, which 35 may be used alone or in combination with any other aspect, a surface cleaning apparatus may have a first or primary airflow path through which dirt laden air travels from a dirty air inlet to a clean air outlet. The first airflow path includes a suction motor and an air treatment member. The surface 40 cleaning apparatus may be powered by an onboard energy source, such as a battery pack or other energy storage member. The energy storage member may include a chemical battery, such as a rechargeable battery. Some batteries, such as lithium-ion batteries, may produce heat while being 45 charged and/or discharged (e.g. while supplying power to an electric motor).

As disclosed herein, a surface cleaning apparatus may also have a second airflow path in which an energy storage chamber is positioned. By drawing ambient air through the <sup>50</sup> second airflow path at or through the chamber in which the energy storage member or members are located, cooling of the energy storage members can be promoted. Using ambient air to cool the energy storage member(s), rather than air exiting a suction motor, may further promote cooling of the <sup>55</sup> energy storage member since the ambient air may be cooler than exhaust air that has passed through or by the suction motor.

In addition, air exiting the suction motor may contain entrained dirt (e.g., carbon from the suction motor or dirt 60 that was not removed by the air treatment member because, inter alia, the user removed a pre-motor filter). The dirt particles may become trapped in the airflow path and/or energy storage chamber, reducing the volume of the air channel available for cooling air to flow through and/or 65 coating the batteries and thereby acting as insulation to reduce the heat transfer from the batteries to air flowing past

the batteries. Using ambient air to cool the energy storage member(s) may reduce clogging of the cooling airflow channels around the energy storage member(s) to provide effective cooling for a longer period of time.

An additional fan unit may be provided in the second air flow path thereby enable the energy storage members to be cooled more effectively by drawing in additional ambient air. This may decrease damage that may occur to the energy storage members because of excessive heating during use and/or charging, resulting in a longer usable timespan for the hand vacuum clean between charges. The increased efficiency may also result in a longer lifespan of the energy storage members.

In accordance with this broad aspect, there is provided a surface cleaning apparatus having a front end, a rear end, an upper end, a lower end, and first and second laterally spaced apart sides, and comprising:

- (a) a first air flow path extending from a dirty air inlet to a clean air outlet;
- (b) an air treatment member positioned in the air flow path and having an air treatment member air inlet and an air treatment member air outlet;
- (c) a suction motor positioned in the air flow path upstream of the clean air outlet;
- (d) a second air flow path extending from an ambient air inlet to a secondary air outlet;
- (e) an energy storage chamber having at least one energy storage member wherein the energy storage chamber is positioned in the second air flow path; and,
- (f) a fan unit positioned in the second air flow path upstream of the secondary air outlet,
- wherein, in operation, the fan unit draws ambient air into the second air flow path via the ambient air inlet.

In any embodiment, the second airflow path may be fluidically isolated from the first airflow path.

In any embodiment, the energy storage chamber may be thermally isolated from the first airflow path.

In any embodiment, the surface cleaning apparatus may comprise a control system capable of detecting an operating condition of the surface cleaning apparatus and then selectively activating the fan unit based on the operating condition. The operating condition may be a charging status of the at least one energy storage member, and the control system may be operable to activate the fan unit when the at least one energy storage member is charging. Alternately, or in addition, the operating condition may be an operational status of the surface cleaning apparatus, and the control system may be operable to activate the fan unit when the suction motor is actuated.

In any embodiment having a control system, the operating condition may be a temperature of the at least one energy storage member, and the control system may be operable to activate the fan unit when the temperature of the at least one storage member exceeds a predefined threshold temperature.

In any embodiment having a control system, the surface cleaning apparatus may comprise a temperature sensor positioned to measure a temperature of the at least one energy storage member, and the control system may be operable to activate the fan unit when the measured temperature exceeds a predefined threshold temperature.

In any embodiment, the surface cleaning apparatus may comprise a filter positioned in the second airflow path at the ambient air inlet.

In any embodiment, the surface cleaning apparatus may comprise a control system capable of controlling an oper-

55

60

ating condition of the surface cleaning apparatus, wherein the control system is in fluid contact with the second airflow path.

In any embodiment, the surface cleaning apparatus may comprise a main body and the energy storage chamber may <sup>5</sup> be removably mounted to the main body; the energy storage chamber may comprises a moveable portion having an engagement member, the engagement member being moveable between a locked position and an unlocked position, wherein when the energy storage chamber is mounted to the main body and the engagement member is in the locked position the engagement member prevents the energy storage chamber being removed from the main body and when the energy storage chamber is in the unlocked position the energy storage member is in the unlocked position the energy storage member is removable from the main body; and, the moveable portion may define a fan unit housing enclosing the fan unit.

In any embodiment, the energy storage chamber may  $_{20}$  comprise a moveable portion that defines a fan unit housing enclosing the fan unit.

In any embodiment, an exterior surface of the at least one energy storage member may be free of an electrically insulating coating.

In any embodiment, the energy storage chamber may comprise a housing manufactured of a thermally conductive plastic.

In any embodiment, the energy storage chamber may comprise a housing defining an outer perimeter of the energy <sup>30</sup> storage chamber; the energy storage chamber may have a dovetail recess that is recessed inward of the outer perimeter of the energy storage chamber; and the energy storage chamber is mountable to a main body of the surface cleaning apparatus by the dovetail recess.

In accordance with another aspect of this disclosure, which may be used alone or in combination with any other aspect, it may be desirable for the energy storage members to be cooled using ambient air without the need for an 40 additional fan unit. This may reduce or eliminate power drawn by the fan unit to further increase the battery efficiency. Omitting the fan unit could also provide a reduced overall weight for the surface cleaning apparatus, for example, so it can be more easily carried by a user while 45 cleaning one or more surfaces. For example, air may be drawn through the energy storage chamber using a venture. Accordingly, when the suction motor is actuated, the airflow created by the suction motor will cause air to be drawn through a second airflow path through the energy storage 50 chamber via the venture.

In accordance with this broad aspect, there is provided a surface cleaning apparatus having a front end, a rear end, an upper end, a lower end, and first and second laterally spaced apart sides, and comprising:

- (a) a first airflow path extending from a dirty air inlet to a clean air outlet;
- (b) an air treatment member positioned in the airflow path and having an air treatment member air inlet and an air treatment member air outlet;
- (c) a suction motor positioned in the airflow path upstream of the clean air outlet;
- (d) a second airflow path extending from an ambient air inlet to a secondary air outlet;
- (e) an energy storage chamber having at least one energy 65 storage member wherein the energy storage chamber is positioned in the second air flow path; and,

(f) a venturi connecting the first and second airflow paths whereby airflow through the first airflow path draws air through the second air flow path.

In any embodiment, the secondary air outlet may be positioned downstream of the at least one energy storage member.

It will be appreciated by a person skilled in the art that an apparatus or method disclosed herein may embody any one or more of the features contained herein and that the features may be used in any particular combination or sub-combination.

These and other aspects and features of various embodiments will be described in greater detail below.

## BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding of the described embodiments and to show more clearly how they may be carried into effect, reference will now be made, by way of example, to the accompanying drawings in which:

FIG. **1** is a top front perspective view of a hand vacuum cleaner in accordance with an embodiment;

FIG. **2** is a bottom front perspective view of the hand vacuum cleaner of FIG. **1**;

FIG. **3** is a top front perspective view of the hand vacuum cleaner of FIG. **1** with an energy storage chamber partially removed;

FIG. **4** is a top front perspective view of the hand vacuum cleaner of FIG. **1** with the energy storage chamber fully removed:

FIG. **5** is a bottom rear perspective view of the hand vacuum cleaner of FIG. **1** with the energy storage chamber fully removed;

FIG. 6 is a top front perspective view of an energy storage chamber for a hand vacuum cleaner in accordance with an embodiment;

FIG. **7** is a top rear perspective view of the energy storage chamber of FIG. **6**;

FIG. **8** is a front perspective view of the energy storage chamber of FIG. **6** with a latch member in a partially open position;

FIG. 9 is a perspective sectional view of the energy storage chamber of FIG. 6, taken along line 9-9 in FIG. 6;

FIG. **10** is a perspective sectional view of the energy storage chamber of FIG. **6**, taken along line **10-10** in FIG. **6**;

FIG. **11** is a perspective sectional view of the energy storage chamber of FIG. **6**, taken along line **10-10** in FIG. **6** with the energy storage members removed;

FIG. 12 is a perspective sectional view of the energy storage chamber of FIG. 6, taken along line 12-12 in FIG. 6;

FIG. 13A is a cross-section view of the hand vacuum cleaner of FIG. 1, taken along line 13-13 in FIG. 1;

FIG. **13**B is a cross-section view of the hand vacuum cleaner of FIG. **1**, taken along line **13-13** in FIG. **1**, showing the front portion of the energy storage chamber in an unlocked position;

FIG. **13**C is an enlarged view of the lower right portion of FIG. **13**A:

FIG. 13D is an enlarged view of the lower right portion of FIG. 13B; and

FIG. **14** is a partial schematic view of a conduit connecting the first and second air flow paths.

The drawings included herewith are for illustrating various examples of articles, methods, and apparatuses of the teaching of the present specification and are not intended to limit the scope of what is taught in any way.

#### DESCRIPTION OF EXAMPLE EMBODIMENTS

Various apparatuses, methods and compositions are described below to provide an example of an embodiment of each claimed invention. No embodiment described below limits any claimed invention and any claimed invention may 10 cover apparatuses and methods that differ from those described below. The claimed inventions are not limited to apparatuses, methods and compositions having all of the features of any one apparatus, method or composition described below or to features common to multiple or all of the apparatuses, methods or compositions described below. It is possible that an apparatus, method or composition described below is not an embodiment of any claimed invention. Any invention disclosed in an apparatus, method or composition described below that is not claimed in this  $_{20}$ document may be the subject matter of another protective instrument, for example, a continuing patent application, and the applicant(s), inventor(s) and/or owner(s) do not intend to abandon, disclaim, or dedicate to the public any such invention by its disclosure in this document.

The terms "an embodiment," "embodiment," "embodiments," "the embodiment," "the embodiments," "one or more embodiments," "some embodiments," and "one embodiment" mean "one or more (but not all) embodiments of the present invention(s)," unless expressly specified oth- 30 erwise.

The terms "including," "comprising" and variations thereof mean "including but not limited to," unless expressly specified otherwise. A listing of items does not imply that any or all of the items are mutually exclusive, unless 35 expressly specified otherwise. The terms "a," "an" and "the" mean "one or more," unless expressly specified otherwise.

As used herein and in the claims, two or more parts are said to be "coupled", "connected", "attached", or "fastened" where the parts are joined or operate together either directly 40 or indirectly (i.e., through one or more intermediate parts), so long as a link occurs. As used herein and in the claims, two or more parts are said to be "directly coupled", "directly connected", "directly attached", or "directly fastened" where the parts are connected in physical contact with each 45 other. None of the terms "coupled", "connected", "attached", and "fastened" distinguish the manner in which two or more parts are joined together.

Furthermore, it will be appreciated that for simplicity and clarity of illustration, where considered appropriate, referonce numerals may be repeated among the figures to indicate corresponding or analogous elements. In addition, numerous specific details are set forth in order to provide a thorough understanding of the example embodiments described herein. However, it will be understood by those of ordinary skill in the art that the example embodiments described herein may be practiced without these specific details. In other instances, well-known methods, procedures, and components have not been described in detail so as not to obscure the example embodiments described herein. Also, 60 the description is not to be considered as limiting the scope of the example embodiments described herein.

Referring to FIGS. 1 to 5 and 13, an exemplary embodiment of a surface cleaning apparatus is shown generally as 1000. The surface cleaning apparatus shown includes a 65 secondary airflow path in through which ambient air is drawn to cool an energy storage chamber 1100.

In the illustrated embodiment, the surface cleaning apparatus is a hand vacuum cleaner, which may also be referred to also as a "handvac" or "hand-held vacuum cleaner". As used herein, a hand vacuum cleaner is a vacuum cleaner that can be operated to clean a surface generally one-handedly. That is, the entire weight of the vacuum may be held by the same one hand used to direct a dirty air inlet of the vacuum cleaner with respect to a surface to be cleaned. For example, the handle and a clean air inlet may be rigidly coupled to each other (directly or indirectly) so as to move as one while maintaining a constant orientation relative to each other. This is to be contrasted with canister and upright vacuum cleaners, whose weight is typically supported by a surface (e.g. a floor) during use. It will be appreciated that surface cleaning apparatus 1000 may alternately be any surface cleaning apparatus, such as an upright surface cleaning apparatus, a stick vac, a canister surface cleaning apparatus, an extractor or the like. It will also be appreciated that the surface cleaning apparatus may use any configuration of the operating components and the airflow paths exemplified herein.

As exemplified in FIGS. 1 to 5 and 13, surface cleaning apparatus 1000 includes a main body 1010 having a housing, 25 a handle 1020, an air treatment member 1060 connected to the main body 1010, a dirty air inlet 1030, a clean air outlet 1040, and an air flow path extending between the dirty air inlet and the clean air outlet, which may be referred to as a first or primary air flow path.

Surface cleaning apparatus 1000 has a front end 1002, a rear end 1004, an upper end or top 1006, and a lower end or bottom 1008. In the embodiment shown, dirty air inlet 1030 is at an upper portion of the front end 1002 and clean air outlet 1040 is at an upper portion of the rear end 1004. It will be appreciated that the dirty air inlet 1030 and the clean air outlet 1040 may be provided in different locations.

A suction motor **1050** is provided to generate vacuum suction through the first air flow path. In some embodiments, the suction motor **1050** is positioned downstream from the air treatment member **1060**, although it may be positioned upstream of the air treatment member **1060** (e.g., a dirty air motor) in alternative embodiments.

The air treatment member **1060** is configured to remove particles of dirt and other debris from the airflow and/or otherwise treat the airflow. Any air treatment member or members known in the art may be used. For example, the surface cleaning apparatus may use one or more cyclones, bags, screens, physical filter media (e.g., foam, felt, HEPA) or the like.

As exemplified, the air treatment member **1060** comprises a cyclone assembly having a single cyclonic cleaning stage with a single cyclone chamber **1062** and a dirt collection region **1064** external to the cyclone chamber. The cyclone chamber **1062** and dirt collection region **1064** may be of any configuration suitable for separating dirt from an air stream and collecting the separated dirt, respectively. The cyclone chamber **1062** may be oriented in any direction.

In alternative embodiments, the cyclone assembly may include two or more cyclonic cleaning stages arranged in series with each other. Each cyclonic cleaning stage may include one or more cyclone chambers (arranged in parallel or series with each other) and one or more dirt collection chambers, of any suitable configuration. The dirt collection chamber or chambers may be external to the cyclone chambers, or may be internal the cyclone chamber and configured as a dirt collection area or region within the cyclone chamber. In the illustrated embodiment, the dirty air inlet **1030** of the hand vacuum cleaner **1000** is the inlet end **1032** of an inlet conduit **1036**. Optionally, inlet end **1032** of the conduit **1036** can be used as a nozzle to directly clean a surface. Alternatively, or in addition to functioning as a nozzle, inlet 5 conduit **1036** may be connected or directly connected to the downstream end of any suitable accessory tool such as a rigid air flow conduit (e.g., an above floor cleaning wand), a crevice tool, a mini brush, and the like.

As exemplified, power may be supplied to the suction 10 motor **1050** and other electrical components of the hand vacuum cleaner **1000** from an onboard energy storage member which may include, for example, one or more batteries **1150** or other energy storage device. In the illustrated embodiment, the hand vacuum cleaner **1000** includes an 15 energy storage chamber **1100**.

A power switch **1070** may be provided to selectively control the operation of the suction motor (e.g. either on/off or variable power levels or both), for example by establishing a power connection between the batteries **1150** and the 20 suction motor **1050**. The power switch **1070** may be provided in any suitable configuration and location, including a button, rotary switch, sliding switch, trigger-type actuator and the like.

The hand vacuum cleaner also includes a clean air outlet 25 at the outlet end of the airflow path. The clean air outlet may be located at any position on the surface cleaning apparatus. As exemplified, air may exit the hand vacuum cleaner **1000** via a grill located in an upper portion of the main body (e.g., via an air outlet **1040** provided in the rear end of the main 30 body or a sidewall adjacent the rear end). Alternately, air may exit through a lower portion of the main body. This may be achieved by conveying the air downwardly through the handle **1020** of the hand vacuum cleaner. Accordingly, at least a portion of the air flow path between the dirty air inlet 35 **1030** and the clean air outlet may flow through the handle **1020**. This may help facilitate a variety of different air flow path configurations and clean air outlet **1040** locations.

In embodiments herein, the hand vacuum cleaner **1000** can also include a second air flow path. The second airflow 40 path may direct or enable a flow of ambient air towards (or through) the energy storage chamber **1100** containing the onboard energy storage members **1150**. Ambient air is air other than that which is passing through the primary airflow path, e.g., air drawn in from the exterior of the surface 45 cleaning apparatus. Some energy storage members, such as lithium-ion batteries, may produce heat while being charged and/or discharged (e.g. while supplying power to an electric motor). The ambient air drawn through the second air flow path can promote cooling of the energy storage members 50 **1150**.

In some embodiments of hand vacuum cleaner **1100**, the second air flow path may be fluidically isolated from the first air flow path. Accordingly, the hand vacuum cleaner **1100** may have separate exhaust outlets for the first air flow path 55 and the second air flow path. Air flowing through the first airflow path can be heated as it passes through the first airflow path by the suction motor **1050**. By isolating the second air flow path, the ambient air that is used to cool the energy storage members **1150** may not be heated by the air 60 from the first air flow path.

Optionally, the second airflow path may also be positioned in the hand vacuum cleaner **1000** so as to be separated from or spaced from the first airflow path to thermally isolate the first and second air flow paths. This may further ensure 65 that the heated air from the first airflow path does not heat the ambient air flowing through the second airflow path.

Optionally, at least a portion of the first and second airflow paths may be positioned adjacent or touching each other but they may be separated by a thermally insulating material.

Similarly, the energy storage chamber **1100** can be positioned in the hand vacuum cleaner **1000** at a location separated from the first airflow path. The energy storage chamber **1100** may be thermally isolated from the first air flow path to prevent the heated air from the first air flow path from heating the energy storage chamber **1100**, and in turn the batteries **1150**.

As exemplified, the energy storage chamber **1100** is mounted to a lower rear portion of the main body **1010**. Similarly, the second airflow path is positioned in the lower rear portion of the main body **1010**. Accordingly, both the energy storage chamber **1100** and the second airflow path may be isolated from the first airflow path.

Alternatively, the first air flow path may pass near to one or both of the energy storage chamber **1100** and the second air flow path. For example, the first air flow path may exit through a lower portion of the main body **1010**. In such cases, the first airflow path may come into thermal contact with one or both of the energy storage chamber **1100** and the second airflow path when they are also positioned in the lower portion of the main body **1010**. In such cases, a thermal barrier (e.g., a thermal insulating material) may be provided between the airflow paths.

FIGS. 6 to 12 illustrate an exemplary embodiment of the energy storage chamber 1100. In the example illustrated, the second air flow path is defined by the energy storage chamber 1100. Accordingly, the energy storage chamber 1100 has both the air inlet to and the air outlet from the second air flow path.

Alternatively, the second airflow path may be defined at least in part by the main body **1010** of the hand vacuum cleaner. Accordingly, the second air flow path may include portions that pass through the main body **1010** and the energy storage chamber **1100**. Accordingly, the air inlet to and/or the air outlet from the second airflow path may be part of the main body **1010**. In such an embodiment, the portion of the second airflow path in the energy storage chamber may be connected to the portion of the second airflow path in the main body when the energy storage member is present in the main body. For example, if the energy storage chamber is removably mounted to the main body, a gasket or the like may be provided to provide an airtight seal between the portions of the second airflow paths.

The second airflow path generally extends from an ambient air inlet **1130** to a secondary air outlet **1140**. In the example shown, the second air flow path passes through the interior **1128** of the energy storage chamber **1100**. This may promote cooling of the batteries **1150** through direct contact with ambient air flowing through the second air flow path.

Alternatively, the second air flow path may not enter the energy storage chamber **1100**. Instead, the energy storage chamber **1150** may be positioned in the second air flow path and the second air flow path may direct airflow at or along one or more walls of the energy storage chamber **1150**. By directing a stream of air directly at, or at an angle to, a wall of the energy storage chamber **1150**, any boundary layer of air (which may act as an insulator) or laminar flow along a wall of the battery chamber **1150** is disrupted, thereby enabling enhanced cooling. In such a case, it will be appreciated that the exterior surface of the energy storage chamber may be provided with cooling fins.

Optionally, operating components of the hand vacuum cleaner 1000 may be positioned in fluid contact with the

second airflow path. This may also allow at least some of the ambient air being drawn into the hand vacuum cleaner **1000** to flow over, and optionally help cool, operating components that are located in contact with the second air flow path. Examples of such components may include controllers, circuit boards, other internal electronics and the like. One example of such electronics can include a printed circuit board (PCB) provided to control optional information display device and/or power switch. Optionally, the operating component may be in a housing and the air may flow over the housing. In such a case, it will be appreciated that the exterior surface of the housing may be provided with cooling fins.

Optionally, a filter may be positioned in the second <sup>15</sup> airflow path upstream of the energy storage chamber. For example, the filter may be positioned at the ambient air inlet. The filter may prevent dirt and debris entrained in the ambient air from entering the second air flow path and/or energy storage chamber and potentially clogging air chan-<sup>20</sup> nels therethrough. The filter may be any suitable type of filter such as a foam filter, felt filter, HEPA filter, other physical filter media, electrostatic filter, and the like.

The energy storage chamber **1100** has a housing **1120** that includes a main body **1122** and an optional front portion 25 **1170**. The housing **1120** may define an interior **1128** of the energy storage chamber **1100**. The front portion **1170** may be mounted to the main body **1122** to retain the batteries **1150** within the interior **1128** of the energy storage chamber **1100**. 30

Optionally, energy storage chamber 1100 may be openable. In accordance with such an embodiment, the front portion 1170 may be removably or moveably (e.g., pivotally) mounted to the main body 1122. A lock may be provided to enable the front portion to be opened. The lock 35 may comprise first and second engagement members provided on the front portion and the remainder of the energy storage chamber 1100. As exemplified, the front portion 1170 can include protruding members or tabs 1178 that engage grooves 1180 in the main body 1122 of the housing. 40 The tabs 1178 and grooves 1180 may provide a friction fit securing the front portion 1170 to the main body 1122. In order to disengage the front portion 1170 from the main body 1122, the protrusions 1178 can be depressed so they no longer engage the grooves 1180. The front portion 1170 may 45 then be removed from the main body 1122. This may provide access to the interior 1128 of the energy storage chamber 1100, e.g. to replace or recycle the batteries 1150. Alternately, any other portion of the energy storage chamber may be openable.

Alternatively, the energy storage chamber may not be openable, e.g., the front portion **1170** may be fixed to the main body **1122**. The energy storage chamber **1100** may then be discarded as a unit.

One or more energy storage members **1150** can be 55 retained in the interior **1128** of the chamber **1100**. The energy storage members **1150** function as onboard power sources for the hand vacuum cleaner **1000**. In general, the power sources may be any suitable device, including, for example one or more batteries. Optionally, the batteries may 60 be rechargeable or may be replaceable, non-rechargeable batteries.

Optionally, power may be supplied to the hand vacuum cleaner **1000** by an electrical cord connected to the hand vacuum cleaner **1000** (not shown) that can be connected to 65 a standard wall electrical outlet. The power from the electrical cord may also serve to recharge the batteries **1150**. In

some instances, the batteries **1150** may be recharged while the vacuum cleaner **1000** is operational.

The energy storage chamber **1100** may include any suitable number of energy storage members **1150**, and may include, for example, lithium ion battery cells. Any number of cells may be used to create a power source having a desired voltage and current, and any type of battery may be used, including NiMH, alkaline, and the like. Energy storage chamber **1100**, which may be referred to as a battery pack, may be electrically connected to the hand vacuum cleaner **1000** by any means known in the art.

The battery pack **1100** may have a power coupling for supplying power (e.g. charging) the cells **1150**. Any suitable power coupling may be used, for example, a female coupling configured to receive a male coupling of an electrical cord that is connectable to a source of AC or DC power, such as a household power socket.

The interior **1128** of the battery pack **1100** may include alignment members to maintain the batteries **1150** in place in the interior **1128**. A plurality of ribs **1154** may extend or project from the inner sidewalls **1156** of the housing **1120**. The ribs **1154** can define battery-receiving regions **1158** of the battery pack **1100**. The ribs may extend in the direction of flow through the energy storage chamber.

Each battery-receiving region **1158** can be shaped to receive a single battery cell **1150**. The ribs **1154** can align the batteries **1150** within the energy storage chamber **1100** and retain the batteries **1150** in place. Optionally, the batteries **1150** may be spot-welded to the ribs **1154** to secure the batteries **1150** in place.

The ribs **1154** can also define a plurality of air channels **1152** for the battery pack **1100**. The air channels **1152** can extend along the batteries **1150** when the batteries **1150** are positioned in the battery pack **1100**. Air entering the ambient air inlet **1130** can pass through the air channels **1152** and contact the exterior surface of the batteries **1150** to promote cooling of the batteries **1150**.

In the example illustrated, the air channels **1152** extend axially along the length of the batteries **1150**. This may expose a large area of the surface of the batteries **1150** to the ambient air flowing through the second air flow path. In general, the air channels **1152** may be provided in any suitable configuration and location within the energy storage chamber **1100**, for instance extending laterally across the batteries **1150**.

The housing **1120** of the energy storage chamber **1100** may include electrically insulating members that enclose the batteries **1150**. For example, the housing **1120** itself may be manufactured of electrically insulating materials such as plastic. This may electrically insulate the batteries **1150** within the energy storage chamber **1100**.

In some cases, the housing 1120 may be thermally conductive. A thermally conductive housing 1120 permits heat transfer between the interior 1128 of the energy storage chamber 1100 and ambient air outside the hand vacuum cleaner 1100. This may further promote cooling of the batteries 1150.

The housing **1120** may be manufactured of plastics that are both electrically insulative and thermally conductive. This may protect the batteries **1150** from unwanted electrical contacts while facilitating cooling.

The ribs **1154** holding the batteries **1150** in place within the housing **1120** can also ensure that the batteries **1150** remain separated from one another. The ribs **1154** may thus isolate the individual battery cells **1150** and ensure there is no direct electrical contact between the battery cells **1150**. This may allow the bare metal casing of the batteries **1150**  to be exposed when positioned in the energy storage chamber **1100**. In other words, the exterior surface of the batteries **1150** positioned in the energy storage chamber **1100** may be free of any electrically insulative coatings.

Electrically insulative coatings may serve to thermally 5 insulate the batteries **1150**. By exposing the bare metal casing of the batteries **1150** to air flowing through the second air flow path (i.e. through air flow channels **1152**) the heat transfer between the batteries **1150** and the ambient air may be improved. Therefore, using an energy storage chamber 10 that enables the batteries to be uncoated may assist in cooling the batteries.

Optionally, one or more thermally conductive heat transfer members may be positioned to contact the batteries **1150**. The heat transfer members may act as heat sinks for the 15 batteries **1150**. The heat transfer member may be manufactured of any suitable thermally conductive material, such as metal.

In some embodiments, the hand vacuum cleaner **1100** may include a fan unit in the second air flow path. The fan 20 unit can be operated to draw ambient air into the second airflow path via the ambient air inlet **1130**.

In the example illustrated, the fan unit **1174** is provided by the battery pack **1100**. Alternatively, the fan unit **1174** may be separate from the battery pack **1100**. For example, if the 25 second airflow path extends through a portion of the main body, then the fan unit **174** may be provided in the main body.

The fan unit **1174** may be positioned at any location upstream of the secondary air outlet **1140** and is preferably 30 downstream of the energy storage members.

Providing the hand vacuum cleaner **1100** with a fan unit **1174** in addition to the suction motor positioned in the first airflow path may increase the weight of the hand vacuum cleaner **1100**. However, operation of the fan unit **1174** 35 ensures that more ambient air is drawn through the second air flow path to promote cooling of the batteries **1150**.

Cooling the batteries can reduce or prevent damage to the batteries from overheating during charging and/or discharging. The can provide a longer usable timespan for the hand 40 vacuum cleaner 1100 between recharge or replacement of the batteries 1150. Additionally, this may also extend the overall usable lifespan of rechargeable batteries 1150 by reducing the number of battery discharge cycles.

The fan unit **1174** can be powered by the batteries **1150** in 45 the battery pack **1100**. As a result, the fan unit **1174** may increase the power drawn from the batteries **1150** while it is operational. Nonetheless, the increased efficiency of the batteries **1150** because of ambient air-cooling will typically be greater than the power required by the fan unit **1174**. The 50 fan unit may be similar to those used to cool a CPU of a computer or the like. As such, the fan unit may draw little power and may not noticeably effect the operational time of a surface cleaning apparatus on a single battery charge.

In some embodiments, the fan unit **1174** may be activated 55 when the vacuum cleaner **1100** is powered on. Alternatively or in addition, the fan unit **1174** may be selectively activated based on the operating conditions of the vacuum cleaner **1100**. Selectively activating the fan unit **1174** may reduce the amount of power drawn from the batteries **1150** by operation 60 of the fan unit **1174**.

The hand vacuum cleaner **1100** may include a controller or control system that can monitor and detect one or more operating conditions of the vacuum cleaner **1100**. The control system may activate or deactivate the fan unit **1174** 65 based on the one or more operating conditions detected. The control system may also adjust the rate or rotation of the fan

unit, e.g., the power supplied to the fan unit, based on the operating conditions of the hand vacuum cleaner **1100**.

Batteries **1150** may tend to heat up when being charged or discharged. Accordingly, the fan unit **1174** may be activated to promote the cooling of the batteries **1150** during operations where the batteries **1150** are expected to heat up.

In some cases, the fan unit **1174** may be activated based on a charging status of the batteries **1150** in the energy storage chamber **1100**. For example, the fan unit **1174** may be activated when the batteries **1150** are being charged.

In some cases, the fan unit **1174** may be activated when the batteries **1150** are being discharged. For example, the control system may determine that the hand vacuum cleaner is performing a cleaning operation (e.g., the control system may determine that the suction motor **1050** has been actuated). The control system may then activate the fan unit **1174** when the suction motor **1050** is active. When the temperature of the batteries **1150** increases, the battery efficiency may decrease. Accordingly, activating the fan unit **1174** when the batteries are being discharged may prolong the discharge period for a single charge.

In some cases, the fan unit **1174** may only be activated when certain operational parameters are met. Rather than activating the fan unit **1174** any time the batteries **11550** are discharging or charging, the control system may detect an operational condition of the vacuum cleaner **1000** indicating that cooling of the batteries **1150** is desired.

In some cases, a surface cleaning apparatus may have different operating modes (e.g., a low power mode wherein the suction motor is operated on a low power draw from the batteries and a high power mode wherein the suction motor is operated on a high power draw from the batteries). The fan unit **1174** may not be activated when the batteries **1150** are discharging slowly (e.g., when the surface cleaning apparatus is operating on a low power mode that draws a reduced amount of current from the batteries). Instead, the fan unit may be actuated only when the surface cleaning apparatus is operated at a high power mode, which draws more power from the batteries **1150** than the lower power mode.

In some cases, the fan unit 1174 may not be activated until the batteries 1150 reach a predefined threshold temperature. By waiting to activate the fan unit 1174 until the batteries 1150 reach a predefined temperature, the power drawn by the fan unit 1174 may be further reduced. The hand vacuum cleaner 1000 may include a temperature sensor (not shown) positioned to sense the temperature of the energy storage members 1150 (directly or based on temperature of the energy storage chamber 1100). The control system may activate the fan unit 1174 when the sensor measures a temperature that exceeds the predefined threshold temperature.

For example, where the hand vacuum cleaner **1000** is only briefly activated the batteries **1150** may not reach a temperature at which performance begins to degrade. Accordingly, activating the fan unit **1174** in such cases may draw more power from the batteries **1150** than necessary. By waiting until the batteries **1150** have begun to heat up, the fan unit **1174** can still perform the cooling function without unnecessarily drawing power.

In some cases, the fan unit may be deactivated when a predefined threshold temperature is reached. For example, when the batteries have cooled sufficiently, the fan unit may be deactivated.

In some embodiments, the fan unit **1174** may be omitted. Omitting the fan unit **1174** may reduce the weight of the hand vacuum cleaner **1000** which may improve user maneuverability.

In embodiments omitting the fan unit 1174, airflow through the first airflow path may be used to induce airflow through the second airflow path. For example, a conduit 1085 may extend between the first airflow path 1080 and the second airflow path 1090 (see FIG. 14). The conduit 1085 may create venturi suction through the second airflow path 1090 to induce ambient air to travel through the second airflow path. This induced air flow 1092 may then be used to cool the energy storage members 1150 and/or operating components of the hand vacuum cleaner 1000.

When the energy storage chamber 1100 (and second air flow path 1090) is positioned at the bottom rear of the hand vacuum cleaner 1000 as exemplified, the first air flow path **1080** may be configured to include a section that also flows through or near the bottom rear of the hand vacuum cleaner **1000**. At least a portion of the air flow path between the dirty air inlet 1030 and the clean air outlet 1040 may flow through the handle 1020. This may help facilitate a variety of different air flow path configurations and clean air outlet 20 **1040** locations proximate the energy storage chamber **1100**. This may also allow at least some of the air being exhausted by the suction motor 1050 to flow over the conduit 1085 that extends from the second airflow path 1090 to generate the venturi suction.

The second air flow path 1090 may still pass through, or contact, the energy storage chamber 1100. However, rather than being fluidically isolated from the first air flow path 1080, a conduit 1085 can extend from the second air flow path 1090 towards to the first air flow path 1080. The conduit 30 **1085** may have a first end contacting the second air flow path 1090 and a second end contacting the first air flow path 1080. As air 1082 in the first air flow path 1080 flows across the second end of the conduit 1085, air can be drawn from the second air flow path 1090 towards the first air flow path 35 **1080.** In turn, the low pressure region in the second air flow path 1090 that results can draw ambient air in through the ambient air inlet.

The second end of the conduit 1085 can be arranged to be downstream from the first end of the conduit 1085. That is, 40 the conduit 1085 may have a conduit axis that forms an angle of at most 90 degrees with the direction of air flow 1082 through the first air flow path 1080. This may inhibit air from the first air flow path 1080 from entering the second air flow path 1090 via the conduit 1085. 45

The first end of the conduit 1085 can be positioned to contact the second airflow path 1090 downstream of the energy storage members or downstream of the energy storage chamber 1100. This may ensure that any air from the first air flow path 1080 that might enter the second air flow 50 path 1090 through the conduit 1085 does not enter the energy storage chamber 1100. This may also reduce any heat transfer from the heated exhaust air 1082 flowing through the first air flow path 1080 to the ambient air 1092 that is cooling the energy storage chamber 1100.

In some embodiments, a fan unit 1174 may be employed along with a venturi conduit 1085. This may be particularly advantageous, for example, where the fan unit 1174 is only activated once the batteries 1150 reach a predefined temperature. Prior to the batteries 1150 reaching the predefined 60 temperature, ambient air may still be drawn through the second air flow path 1090 to cool the energy storage members 1150 by operation of the Venturi suction. This induced ambient air flow may prolong the operational period prior to the batteries 1150 reaching the predefined tempera-65 ture threshold. Once the batteries 1150 are heated to the predefined temperature, the fan unit 1174 can then be

activated to increase the volume of ambient air being drawn through the second air flow path 1090.

Optionally, as shown in FIGS. 3-5, the battery pack 1100 may be removable from the rest of the hand vacuum cleaner 1000 using any mechanism known in the art. In alternative embodiments, the energy storage chamber 1100 may be fixed to the main body 1010 and may not be removable.

Any mounting members for enabling a battery pack to be removably mounted may be used. As exemplified, the battery pack 1100 can be removed from the hand vacuum cleaner 1000 by sliding the battery pack 1100 along a track provided in the bottom rear portion of the main body 1010. The main body 1010 has a pair of battery pack mounting members 1026 arranged to receive the battery pack 1100. The battery pack 1100 has a corresponding pair of main body engagement members 1126 (dovetail recesses) that are engagable with the mounting members 1026. The engagement members 1126 and mounting members 1026 may form corresponding elements of a dovetail joint. The battery pack 1100 can be mounted to, or removed from, the main body 1010 by sliding the engagement members 1126 along the mounting members 1026.

As exemplified, the engagement members 1126 can be recessed into the outer perimeter 1124 of the housing 1120. That is, the engagement members 1126 may define a recessed portion of the housing 1120 that extends inwards from the outer face 1124 of the housing 1120. Alternatively, the engagement members 1126 may be flush with or extend from the perimeter 1124 of the housing 1120.

In the example shown in FIG. 9, the recessed engagement members 1126 extend into the interior 1128 of the energy storage chamber 1100. The engagement members 1126 may extend into the energy storage chamber 1100 at least partially within the height of the batteries 1150. By extending into the interior 1128, the engagement members 1126 may reduce the volume of the air flow channels **1152**. However, recessing the engagement members 1126 may provide a more compact overall form for the energy storage chamber 1100

The hand vacuum cleaner 1000 may also include a battery pack lock to secure the energy storage chamber 1100 to the main body 1010. In the example shown, the energy storage chamber 1100 includes a lock member 1172 provided on the top of battery release unit 1160. The lock member 1172 may be a latch that protrudes out of the perimeter of the housing 1120. The main body 1010 has a corresponding engagement region 1028. The lock member 1172 may extend into the engagement region 1028 and prevent the energy storage chamber 1100 from being removed from the hand vacuum cleaner 1000.

The lock member 1172 may be moveable between a locked position (see FIGS. 6 and 7) in which the lock member 1172 extends above the surface of the housing 1120 and an unlocked position (see FIG. 8) in which the lock member 1172 recedes into a recess of the front portion 1170. To move the lock member 1172 between the locked and unlocked position, the battery release unit 1160 may be rotated slightly. In the example shown, the battery release unit 1160 may be rotated by an angle of about 7 degrees or so to transition the lock member 1172 from the locked position to the unlocked position. As shown in FIGS. 13A and 13C, when the battery pack 1100 is mounted to the main body 1010 and the lock member 1172 is in the locked position, the lock member 1172 is received in the engagement region 1028. The lock member 1172 and engagement region 1028 can thus prevent the battery pack 1100 from being slid off the main body 1010. When the lock member

1172 is moved to the unlocked position (see FIGS. 13B and 13D) the battery pack 1100 can be slid off the main body 1010, since the lock member 1172 no longer contacts the engagement region 1028.

The battery release unit 1160 may be biased to the locked 5 position. A user may adjust the release unit 1160 to the unlocked position in order to remove the battery pack 1100. The battery release unit 1160 may be openably connected (e.g., pivotally openable or removably mounted) to the rest of the energy storage chamber using any suitable mecha-10 nism, including a hinge or other suitable device. A user may move the release unit 1160 to the unlocked position by grasping the underside of the release unit 1160 and rotating it to move the lock member 1172 to the unlocked position. Optionally, the battery release unit 1160 may be secured in 15 the closed position using any suitable type of locking mechanism, including a latch mechanism that may be released by a user.

In the embodiment of FIGS. 6 to 13, the battery release unit 1160 may be opened by pivoting it about a hinge 20 assembly from the locked/closed position to the unlocked/ open position. The battery release unit 1160 may be secured in the closed position by a friction fit, and/or by a latch member or other suitable locking mechanism. Preferably, the battery release unit 1160 may include at least one release 25 energy storage chamber is thermally isolated from the first actuator so that a user may unlock the latch member 1172 or release unit 1160 from the closed position, e.g. by depressing the actuator.

In some embodiments, the battery release unit 1160 may also enclose the fan unit 1174. For example, the battery 30 release unit 160 may comprise or consist of the fan unit housing. The battery release unit 1160 may define a fan housing 1162 that provides a receiving space for the fan unit 1174. By mounting the fan unit 1174 in the release unit 1160, the fan unit 1174 can be positioned outside of the main body 35 1122 of the energy storage chamber 1100. At the same time, the fan housing 1162 may act as a finger guard to prevent a user from accidentally contacting the fan unit 1174 in operation.

provide a more compact form for instances when the fan unit 1174 may be omitted. Additionally, this allows the fan unit 1174 to be positioned apart from, and downstream of, the batteries 1150 in the energy storage chamber 1100.

It will be appreciated that a filter may be provided at the 45 air inlet and/or the air outlet of the second airflow path.

As used herein, the wording "and/or" is intended to represent an inclusive-or. That is, "X and/or Y" is intended to mean X or Y or both, for example. As a further example, "X, Y, and/or Z" is intended to mean X or Y or Z or any 50 combination thereof.

While the above description describes features of example embodiments, it will be appreciated that some features and/or functions of the described embodiments are susceptible to modification without departing from the spirit and 55 principles of operation of the described embodiments. For example, the various characteristics which are described by means of the represented embodiments or examples may be selectively combined with each other. Accordingly, what has been described above is intended to be illustrative of the 60 claimed concept and non-limiting. It will be understood by persons skilled in the art that other variants and modifications may be made without departing from the scope of the invention as defined in the claims appended hereto. The scope of the claims should not be limited by the preferred 65 embodiments and examples, but should be given the broadest interpretation consistent with the description as a whole.

The invention claimed is:

1. A surface cleaning apparatus having a front end, a rear end, an upper end, a lower end, and first and second laterally spaced apart sides, and comprising:

- (a) a first airflow path extending from a dirty air inlet to a clean air outlet;
- (b) an air treatment member positioned in the airflow path and having an air treatment member air inlet and an air treatment member air outlet;
- (c) a suction motor positioned in the airflow path upstream of the clean air outlet;
- (d) a second airflow path extending from an ambient air inlet to a secondary air outlet, wherein the second airflow path is fluidically isolated from the first airflow path;
- (e) an energy storage chamber having at least one energy storage member wherein the energy storage chamber is positioned in the second air flow path; and

- (f) a fan unit positioned in the second airflow path upstream of the secondary air outlet,
- wherein, in operation, the fan unit draws ambient air into the second air flow path via the ambient air inlet.

2. The surface cleaning apparatus of claim 1 wherein the air flow path.

3. The surface cleaning apparatus of claim 1 further comprising a control system capable of detecting an operating condition of the surface cleaning apparatus and then selectively activating the fan unit based on the operating condition.

4. The surface cleaning apparatus of claim 3, wherein the operating condition is a charging status of the at least one energy storage member, and the control system is operable to activate the fan unit when the at least one energy storage member is charging.

5. The surface cleaning apparatus of claim 1, wherein the fan unit is actuated when the suction motor is actuated.

6. The surface cleaning apparatus of claim 3 wherein the This may reduce the size of the main body 1122, e.g. to 40 operating condition is a temperature of the at least one energy storage member, and the control system is operable to activate the fan unit when the temperature of the at least one storage member exceeds a predefined threshold temperature.

> 7. The surface cleaning apparatus of claim 3, further comprising a temperature sensor positioned to measure a temperature of the at least one energy storage member, and the control system is operable to activate the fan unit when the measured temperature exceeds a predefined threshold temperature.

> 8. The surface cleaning apparatus of claim 1, further comprising a filter positioned in the second air flow path at the ambient air inlet.

> 9. The surface cleaning apparatus of claim 1, further comprising a control system capable of controlling an operating condition of the surface cleaning apparatus, wherein the control system is in fluid contact with the second air flow path.

10. The surface cleaning apparatus of claim 1, wherein

- (a) the surface cleaning apparatus comprises a main body and the energy storage chamber is removably mounted to the main body;
- (b) the energy storage chamber comprises a moveable portion having an engagement member, the engagement member being moveable between a locked position and an unlocked position, wherein when the energy storage chamber is mounted to the main body and the

engagement member is in the locked position the engagement member prevents the energy storage chamber being removed from the main body and when the energy storage chamber is mounted to the main body and the engagement member is in the unlocked position 5 the energy storage member is removable from the main body; and,

(c) the moveable portion defines a fan unit housing enclosing the fan unit.

**11**. A surface cleaning apparatus having a front end, a rear <sup>10</sup> end, an upper end, a lower end, and first and second laterally spaced apart sides, and comprising:

- (a) a first airflow path extending from a dirty air inlet to a clean air outlet;
- (b) an air treatment member positioned in the airflow path and having an air treatment member air inlet and an air treatment member air outlet;
- (c) a suction motor positioned in the airflow path upstream of the clean air outlet;
- (d) a second airflow path extending from an ambient air <sub>20</sub> inlet to a secondary air outlet;
- (e) an energy storage chamber having at least one energy storage member wherein the energy storage chamber is positioned in the second air flow path; and
- (f) a fan unit positioned in the second airflow path  $_{25}$  upstream of the secondary air outlet,
- wherein, in operation, the fan unit draws ambient air into the second air flow path via the ambient air inlet, and
- wherein the energy storage chamber comprises a moveable portion that defines a fan unit housing containing  $_{30}$ the fan unit.

**12**. The surface cleaning apparatus of claim **11**, wherein the moveable portion has a locking member releasable securing the energy storage chamber in the surface cleaning apparatus.

**13**. The surface cleaning apparatus of claim **1**, wherein the energy storage chamber comprises a fan unit housing containing the fan unit and the fan unit housing has a locking member releasably securing the energy storage chamber in the surface cleaning apparatus.

14. The surface cleaning apparatus of claim 1, wherein an exterior surface of the at least one energy storage member is free of an electrically insulating coating.

**15**. The surface cleaning apparatus of claim **1**, wherein the energy storage chamber comprises a housing manufactured  $_{45}$  of a thermally conductive plastic.

**16**. A surface cleaning apparatus having a front end, a rear end, an upper end, a lower end, and first and second laterally spaced apart sides, and comprising:

- (a) a first airflow path extending from a dirty air inlet to a clean air outlet;
- (b) an air treatment member positioned in the airflow path and having an air treatment member air inlet and an air treatment member air outlet;
- (c) a suction motor positioned in the airflow path upstream of the clean air outlet:
- (d) a second airflow path extending from an ambient air inlet to a secondary air outlet;
- (e) an energy storage chamber having at least one energy storage member wherein the energy storage chamber is positioned in the second air flow path; and
- (f) a fan unit positioned in the second airflow path upstream of the secondary air outlet,
- wherein, in operation, the fan unit draws ambient air into the second air flow path via the ambient air inlet, and
- wherein the energy storage chamber comprises a housing defining an outer perimeter of the energy storage chamber and the housing is slideable is mountable to a main body of the surface cleaning apparatus.

**17**. A surface cleaning apparatus having a front end, a rear end, an upper end, a lower end, and first and second laterally spaced apart sides, and comprising:

- (a) a first airflow path extending from a dirty air inlet to a clean air outlet;
- (b) an air treatment member positioned in the airflow path and having an air treatment member air inlet and an air treatment member air outlet;
- (c) a suction motor positioned in the airflow path upstream of the clean air outlet;
- (d) a second airflow path extending from an ambient air inlet to a secondary air outlet;
- (e) an energy storage chamber having at least one energy storage member wherein the energy storage chamber is positioned in the second air flow path; and,
- (f) a venturi connecting the first and second airflow paths whereby airflow through the first airflow path draws air through the second air flow path.

**18**. The surface cleaning apparatus of claim **15** wherein the secondary air outlet is positioned downstream of the at least one energy storage member.

**19**. The surface cleaning apparatus of claim **16** wherein the energy storage chamber has a dovetail recess that is recessed inward of the outer perimeter of the energy storage chamber and, the energy storage chamber is mountable to a main body of the surface cleaning apparatus by the dovetail recess.

\* \* \* \* \*